



7-Ply Platform (Greenply)

- 3 Step Calibration
- Virtually void free 7 ply platform
- UV finish available
- FSC Certified

Technical Data:

Thickness tolerance: Based on 19mm, +.1mm/-.6mm
 Moisture Content: < / = 14%
 Square Tolerance: 2 diagonal difference : < / = 3mm
 Glue Certification: CARB Phase II
 Veneer Thickness: .6mm before sanding

<u>19mm Panels</u>	<u>Details</u>	<u>Measurement</u>	<u>Veneer Core</u>
MOR	Parallel	PSI	6843
MOR	Perpendicular	PSI	4304
MOE	Parallel	PSI x 1000	718
MOE	Perpendicular	PSI x 1000	583
Internal Bond	Point of Separation	PSI	153
Linear Expansion	Parallel	Percentage	0.3
Thickness Tolerance	(mm)	+ or -	+ .1, - .6
Screw Holding	Face	lbf	299
Screw Holding	Edge	lbf	295
Urea Formaldehyde Emissions	Urea Formaldehyde	ppm	<.04
Weight per Panel	48" x 96"	lbs	69

Data as of 6-1-2011

All data is based on averages from independent testing performed by, PSI – Professional Service Industries Inc. – Pittsburg Testing Laboratory Division. No liability of any kind will be held or associated with the data listed. The user is to be solely responsible for the final determination of suitability. All materials should be used with cautiousness and unforeseen hazards may exist. While some hazards are explained above, we cannot guarantee that there are no other hazards.